

HCZD260 Paint-booth



Product Features :

Lamp heater, Three fan (2 INLET & 1 OUTLET),

Stainless steel base,

low threshold within one meter outside and inside,

2: Technical parameter

Outside Size (mm)	7000×5200×3370	Front Door(mm)	3000(w)×2600(h)
Inside Size(mm)	6900×3900×2650	Total Power(km)	10+30kv

3: Product Introduce:

Cabin System	Wallboard	EPS (epispastics polystyrene)Colorful Steel Skin Boards 0.326mm, 50mm Thick, Tongue & Groove Style, Compound Construction, Aluminum-alloy Frame. Anti-flame and Heat-Insulation, Galvanized steel roof panel	
	Basement	Galvanized Steel Sheet and Square steel pipe assembling, Grid & embossed plate floor, Three embossed steel ramps.	
Air Circulation System	Inhaling Ventilator	Blower capacity: 22000m ³ /h	Outlet Fan:4kw /1set
		Power: 3kw/set	
		Quantity: 2 sets	
Air Volume: 22000m ³ /h; Air Speed: 0.35m/s, Air Recycling times:280 times/h;			
Purification System	Dual Filtering Structure, The Primary Filter Can Capture Granules Larger than 10μm. Ceiling Filter Capture Granules Bigger than 4μm. Its filtering rate reaches 98%. air pressure balance gauge, TSP≤1.4mg/m ³		
Heating System	Burner	30pc Infrared heating tube	
	Heat Energy Converter	SUS304 Stainless Steel heat exchanger, argon arc welding;	
	Max Temp:80° C, Heating Time:6-8min(20-50°C),		
Light System	Ceiling Light: 24pcs 36w Philips Lamp; 800 Lux		
Controlling System	Spray & Baking Switch, Light Switch, Emergency Stop, Breakdown Alarm		





